










Load span table for 155mm deep beam

Block Density Kg/m ³	Maximum effective span in Meters				Beam case	Beam layout
	Super Imposed Load kN/m ²					
	1.5	2.0	2.5	3.0		
1350	4.362	4.141	3.950	3.782	S515	
1950	4.140	3.949	3.781	3.601		
1350	4.880	4.640	4.431	4.247	S408	
1950	4.649	4.439	4.254	4.091		
1350	5.635	5.369	5.138	4.933	S290	
1950	5.401	5.165	4.958	4.772		
1350	5.349	5.098	4.878	4.684	D640	
1950	5.143	4.918	4.719	4.543		
1350	5.800	5.537	5.306	5.101	D528	
1950	5.605	5.365	5.153	4.965		
1350	5.800	5.800	5.800	5.649	D415	
1950	5.800	5.800	5.731	5.527		
1350	5.800	5.596	5.365	5.160	T765	
1950	5.678	5.437	5.224	5.034		
1350	5.800	5.800	5.733	5.520	T653	
1950	5.800	5.800	5.604	5.405		
1350	5.800	5.800	5.800	5.800	T540	
1950	5.800	5.800	5.800	5.800		

Load Span table based on 65mm screed with no allowance for line and point load from partitions.

Size of block used 440mm x 215mm x 100mm

Please note spans given are for guidance only; please contact a member of Su-Fix for further information.